

# YOUR NEW *ADDITION* imageCLASS LBP7780Cx

**WORKHORSE PLUS RANGE  
– ADVANCE Colour Laser Printer**



The perfect machine to compliment your corporation's existing print structure. Whether it is used as a standalone printer, or built into an MDS solution with the uniFLOW software embedded – the LBP7780Cx will continue to impress.

As with all models in Canon's new "LBP Advanced" range The IMAGECLASS LBP7780Cx is built from the ground up to complement the existing printing environments of large businesses. It features integrated PCL & Genuine Adobe PostScript, MEAP compatibility to allow the embedding of MEAP applications and compatibility with FM Audit & Print Fleet.

## Key Features

### MEAP-Embedded

- With the embedded MEAP environment, users are able to utilise a range of MEAP applications, such as uniFLOW to enhance their workflows and increase productivity.

### Genuine Adobe PostScript, & PCL Compatible

- The LBP7780Cx features genuine Adobe PostScript to ensure the best results when used in a PS environment. Furthermore, it also supports PCL, making it ideal for use in large organisations with established print solutions.

### Low Power Consumption and Quick Start Up

- With Canon's unique On-Demand Fixing System, the LBP7780Cx achieves low power consumption of less than 35 watts (average) in standby and quick start-up, with first page out in less than 11 seconds. Canon's On-Demand Fixing System enables instantaneous heating of the fusing heater only before printing, saving warm-up time. The LBP7780Cx is always ready to print – saving you time and money.

### Enhanced Security

- Organisations can now eliminate unnecessary printing, while ensuring the security of sensitive documents with the LBP7780Cx's Secure Print features. This can be configured using the printer's memory for a server-less solution, or run via uniFLOW, which can be embedded onto the machine via MEAP.

### eRDS capability

- Direct access to e-Maintenance via eRDS, so there is no need for an EMAGENT



### On Demand Fixing

Canon's unique On Demand Fixing system offers low power consumption and fast recovery times from standby mode



### Connectivity

Integrated network connection to easily share amongst many users within the office



### Automatic Image Refinement

Increases the resolution of the print up to an equivalent of 2400 x 600 dpi ensuring that you get a professional looking document every time



### Auto Duplex

Auto duplex for easy double sided printing



### Fast Print Speed

Offering up to 32 ppm print speeds with a 0 sec recovery from sleep mode so you will never be waiting for a print again



### PCL, Genuine Adobe PostScript Support

Supports common printer languages for seamless integration into an existing print solution



### Powered By MEAP

Running MEAP applications such as uniFLOW is no problem with the LBP7780Cx's integrated MEAP environment



### Compatibility with FM Audit / Print Fleet



Compatibility with FM Audit & Print Fleet for easy inclusion into multi-vendor MPS solutions



### Low Power Consumption in Standby

By offering reduced power consumption, Canon Laser Printers will save you money help the environment

### Laser Printers

Canon laser printers combine a range of features and technologies to deliver fast, high quality and reliable printing. So, if you are looking to create professional business documents while reducing your running costs, Canon lasers fit the bill.

Subject to change without notice.

**Canon**

*achieve more.  
beyond technology.*

# imageCLASS LBP7780Cx

## Workhorse plus range – ADVANCE Colour Laser Printer

### Print Specifications

Printing Method	Colour laser beam printing
Fixing Method	On-Demand Fixing
FPOT	A4: 10.4/10.2 sec (Colour/BW)
Print Speed <sup>1</sup>	Mono: A4/Letter: 32/33 ppm Colour: A4/Letter: 32/33 ppm Duplex: A4/Letter: 27.6/28.9 ppm
Resolution	600 dpi × 600 dpi / 9600 dpi (equivalent) × 600 dpi

### Other Features

Warm-up time (when the printer is turned on)	39 sec or less
Recovery time	Approx. 7 sec (engine sleep) / Approx. 30 sec (deep sleep)

### Media Handling

Paper Input (based on 80g/m <sup>2</sup> )	Standard cassette: 500 sheets Multi-purpose tray: 100 sheets Option: 500 sheets Max. paper capacity: 1100 sheets
Paper output (based on 80g/m <sup>2</sup> )	Face-down: 200 sheets
Paper size	Standard cassette: A4/B5/A5/A6/Letter/ Executive/16K/Statement/ Custom (width 101.6–215.9 mm x length 148–297.0 mm): when width is 215.9mm, max length is 279.4mm: when length is 297.0mm, max width is 210.0mm Multi-purpose tray: A4/B5/A5/A6/Letter/Legal/ Executive/Foolscap/16K/Statement/Envelope/ COM-10/Envelope C5/Envelope Monarch/ Envelope DL/3x5 index card/Custom (width 76.2–215.9mm x length 127.0–355.6mm) Option cassette: A4/B5/A5/Letter/Legal/Executive/ Foolscap/16K/Custom (width 148–215.9mm x length 210.0–355.6mm)
Paper weight	Standard cassette: 60–163g/m <sup>2</sup> Multi-purpose tray: 60–216g/m <sup>2</sup> Option cassette: 60–176g/m <sup>2</sup>
Paper type	Plain Paper/Heavy Paper/Transparency/Recycle Paper/Label/Envelope
Print margins	5 mm-top, bottom, left and right (Envelop: 10 mm)
Duplex printing	A4/B5/A5/Letter/Legal/Executive/Foolscap/16K/ Custom (width 148.0–215.9mm x length 210.0–355.6mm) 60–163g/m <sup>2</sup>


### General Features

Memory	Standard: 768MB Maximum: 768MB
Operation mode	Page description language: UFR II, PCL5c, PCL6, Postscript3
Optional ROM	Bar DIMM
Standard font	93 Scalable, 10 bitmap fonts, 136 PS fonts
HDD/SD	8GB SD Card
I/F	USB: USB 2.0 Host x 2, USB 2.0 Device x 1 Network: 10Base-T/100Base-TX/1000Base-T Expansion I/F: SDIO
Compatible operating systems	WindowsXP (32bit/64bit)/Windows Server 2003 (32bit/64bit)/Windows Vista (32bit/64bit)/Windows Server 2008 (32bit/64bit)/Windows 7 (32bit/64bit) Mac OS 10.5.x – Linux, Citrix
Operation panel	5 Line LCD/8 LED/12 Key
Noise level	During operation: Approx. 52 dB (sound pressure) During standby: Approx. 32.4 dB (sound pressure)
Power consumption (W)	Maximum: 1270W or less Operation: Approx. 580W During standby: Approx. 35W During sleep: Approx. 1W or less
Dimensions (W × D × H)	517 mm x 530 mm x 401 mm
Weight (kg) without CRG	Approx. 31.5 kg
Power requirement	220–240V/50–60Hz (±2Hz)
Operating environment	Temperature: 10–30°C Humidity: 20–80%RH (no condensation)

### Toner Specifications

Cartridges <sup>2</sup>	CART333BK: yields 5,000 pages CART332BKII: yields 10,000 pages CART332C / M / Y: yields 8,500 pages
-------------------------	---

1. Print speed may vary with the content of the document and the processing speed of the host computer. Time from when print data is received.
2. In compliance with ISO/IEC 19798  
Subject to change without notice.



LAS-2YOS-1 – 3 year Extended Onsite Service & Support card

canon.com.au/business

Follow us on Twitter @CanonBusinessAU

1800 444 199

2305-v1-02/14

*achieve more.  
beyond technology.*